IN THE CLAIMS:

Please amend the claims as follows:

Claim 1 (Currently Amended): A spherical aberration correcting unit for correcting an aberration caused in an optical beam radiated toward an object to be detected and focused on the object, the unit comprising:

an aberration corrector composed of a plurality of optical members and configured to form the optical beam into a parallel pencil and to correct the aberration caused in the optical beam, the optical members including at least a converging lens and a diverging lens respectively;

a driver configured to drive only [[any]] one of the converging lens and the diverging lens the optical members in an optical axis direction of the optical beam;

a light receiver configured to receive light reflected from the object to produce a light-reception signal from the received light; and

a controller configured to control the driver based on the produced light-reception signal.

Claim 2 (Original): The spherical aberration correcting unit according to claim 1, wherein the object is an optical information recording medium.

Claim 3 (Currently Amended): The spherical aberration correcting unit according to claim 1, wherein a relationship of $0.2 < |f1/f| < 0.82$ is established fulfilled, wherein a composite focal length of the converging lens and the diverging lens of the aberration corrector is f and a

focal length of <u>thus driven one of the converging lens and the diverging lens</u> ~~the driven optical member~~ is f1.

Claim 4 (Original): The spherical aberration correcting unit according to claim 1, wherein the aberration corrector is a collimator lens.

Claim 5 (Original): The spherical aberration correcting unit according to claim 2, wherein the any one of the optical members is composed of a plurality of lenses.

Claim 6 (Currently Amended): The spherical aberration correcting unit according to claim 2, wherein <u>at least one of the converging lens and the diverging lens</u> ~~the collimator lens~~ has an aspheric surface.

Claim 7 (Currently Amended): The spherical aberration correcting unit according to claim 2, wherein a hologram is attached to <u>at least one of the converging lens and the diverging lens</u> ~~the collimator lens~~.

Claim 8 (Currently Amended): An optical pickup for reading and writing information from and to an optical information medium by radiating an optical beam toward the optical information medium, the optical beam being focused on the optical information medium, the optical pickup comprising:

[[an]] a spherical aberration correcting unit for correcting an aberration caused in the optical beam,

wherein the unit comprises:

an aberration corrector composed of a plurality of optical members and configured to form the optical beam into a parallel pencil and to correct the aberration caused in the optical beam, the optical members including at least a converging lens and a diverging lens respectively;

a driver configured to drive only any one of the converging lens and the diverging lens the optical members in an optical axis direction of the optical beam;

a light receiver configured to receive light reflected from the medium to produce a light-reception signal from the received light; and

a controller configured to control the driver based on the produced light-reception signal.

Claim 9 (Original): The optical pickup according to claim 8, wherein the object is an optical information recording medium.

Claim 10 (Currently Amended): The optical pickup according to claim 8, wherein a relationship of 0.2<|f1/f|<0.82 is established fulfilled, wherein a composite focal length of the converging lens and the diverging lens of the aberration corrector is f and a focal length of thus driven one of the converging lens and the diverging lens the driven optical member is f1.

Claim 11 (Original): The optical pickup according to claim 8, wherein the aberration corrector is a collimator lens.

Claim 12 (Currently Amended): A spherical aberration correcting method for correcting an aberration caused in an optical beam radiated toward an object to be detected and focused on the object, the method comprising the steps of:

forming the optical beam into a parallel pencil using a plurality of optical members, including at least a converging lens and a diverging lens respectively, while ~~during which time,~~ correcting the aberration caused in the optical beam;

driving only [[any]] one of the converging lens and the diverging lens ~~the optical members~~ in an optical axis direction of the optical beam;

receiving light reflected from the object to produce a light-reception signal from the received light; and

controlling the driver based on the produced light-reception signal.